

# SUPER PHOS

## METAL CLEANER & SCALE REMOVER



CODE: E08

- FAST ACTING FORMULATION
- LOW FOAM & NON-TAINING
- CLEANS ALUMINIUM & BRIGHT METALS
- DE-RUSTS, DE-SCALES, PROTECTS

### RECOMMENDED USE

Pipe work, tiles, walls, floors, sinks, urinals, toilets, stainless steel, aluminium, concrete, glass and kitchen equipment.

**USE FOR:** Rust and oxide contamination removal, inorganic and hard water deposits, uric acid, scale.

### DIRECTIONS FOR USE

Can be used as supplied or diluted with hot or cold water. Always add chemical to water to avoid splashes.

Use in a well ventilated area.

**Heavy deposits:** Use neat or dilute up to 5:1

**General de-scaling:** Dilute up to 50:1

**Light duty de-scaling:** Dilute up to 100:1

### FOR DE-SCALING CONTAINERS

First apply Super Phos undiluted to the areas of scale build-up. Then fill the container with water and leave to soak for up to four hours, depending on the level of scale build up. Remove liquid and rinse thoroughly.



IN USE  
RISK LEVEL



### PACK SIZES



### HEALTH + SAFETY

**EYES:** Rinse splashes to eyes, wash with water immediately.

**PPE:** Wear protective gloves (acid resistant), protective clothing, eye protection, face protection.

For full Health & Safety information, refer to the Safety Data Sheet.



pH IN USE



PARAGON PRODUCTS (UK) LTD, CHESTERFIELD, S41 9QJ  
01246 944 866 | sales@paragongroup.co.uk  
www.paragongroup.co.uk

CODE: E08/240904